



# Cartridge Filter Dust Collector

## General Construction:

- 12-gauge steel welded unit
- Cartridge cage supports are structural members with cross bracing
- Bag diameter is 4.5" X 96" (120" optional)

## Applications/Industries:

- Manufacturing
- Aerospace
- Metal processing
- Grinding/sanding
- Welding/soldering

## Options:

- Custom tuned fan outlet silencer
- Push button motor start
- Hepa filter discharge
- Flexible configuration



Model*	Cartridges	CFM
2D-CDJ-2	4	2,200
2D-CDJ-3	6	3,300
2D-CDJ-4	8	4,400
2D-CDJ-5	10	5,500
3D-CDJ-3	9	4,500
3D-CDJ-4	12	6,000
4D-CDJ-3	12	6,300
4D-CDJ-4	16	8,400
4D-CDJ-5	20	10,500
4D-CDJ-6	24	12,600
4DD-CDJ-3	12	12,000
4DD-CDJ-4	16	16,000
4DD-CDJ-5	20	20,000

\* Call 717-854-4050 to discuss specific sizing for your application

## Key Features:

- **High Side Entry**- eliminates can velocity problems
- **Wide Cartridge Spacing** – reduces re-entrainment and plugging of filter element
- **Cleaning in Columns**- to prevent dust from accumulating on lower placed cartridges
- **Twin Cleaning Jets**- doubles performance
- **Automatic Alignment** and rigid support for mounting cartridges
- **Twin-Powered Supersonic Nozzles**- provide greater cleaning power
- **Easy Cartridge "Change Out"**-performed outside the filter unit

**Air Dynamics Industrial Systems Corporation**

300 North Queen Street York, PA 17403

Tel: 717-854-4050

E-mail: [sales@airdynamics.net](mailto:sales@airdynamics.net)

Fax: 717-854-4020